

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/020175 A1

(51) International Patent Classification⁷: **G08B 21/00**,
19/02, G01W 1/00

(21) International Application Number:
PCT/US2003/026403

(22) International Filing Date: 20 August 2003 (20.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **THE BOEING COMPANY** [US/US]; 7755 E. Marginal Way South, Seattle, WA 98108 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **COOK, Donald, E.** [US/US]; P.O. Box 3707, MC 13-08, Seattle, WA 98124-2207 (US). **FEIDER, Michael, P.** [US/US]; P.O. Box 3707, MC 13-08, Seattle, WA 98124-2207 (US).

(74) Agents: **WECHKIN, John, M.** et al.; Patent-Sea, P.O. Box 1247, Seattle, WA 98111-1247 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHODS AND SYSTEMS FOR DETECTING ICING CONDITIONS



(57) Abstract: Methods and systems for detecting icing or incipient icing conditions external to a vehicle (100) are disclosed. An apparatus in accordance with one embodiment of the invention includes a temperature sensor (120) configured to direct a first signal corresponding to a temperature of an airstream, and a water content sensor (130) configured to direct a second signal corresponding to a water content of the airstream. A processing unit (140) can receive the first and second signals and, based on at least the first and second signals, provide an indication (150) when at least the first and second signals taken together correspond to an at least incipient icing condition. Accordingly, the system can be installed on aircraft to provide notice to the crew of incipient or existing icing conditions.